

Oven-Controlled Crystal Oscillator YOV3627DP OCXO



Applications

- router
- switching equipment

Features

- Small size, high stability, high frequency
- Aging $\leq \pm 1\text{E-}10/\text{day}$
- Temperature stability $\leq \pm 1\text{E-}10$ (-40°C to 70°C)

Specifications (规格参数)

Item		Technical Specifications
Performance Specifications 性能指标	Frequency 频率	80~100MHz
	Supply Voltage 工作电压	3.3V, 5V, 12V
	Output waveform 波形	Sine Wave/HCMOS
	Frequency Tolerance vs. Operating Temperature Range 温度稳定度	$\leq \pm 0.1$ ppb (best achievable) @ $-40 \sim +70^{\circ}\text{C}$
	Warm up current 启动功耗	$< 6\text{W}$
	Steady Consumption 稳定功耗	$< 2\text{W}$
	Warm up time 启动时间	$< 5\text{min}$
	Voltage Control Characteristics 电压控制特性	Linearity $< 5\%$
		Positive
	short-term stability 短稳	$< 8\text{E-}12 @ 1\text{s}$
Phase Noise 相噪 (@80M)	1Hz	-120dBc/Hz Min.
	10Hz	-150dBc/Hz Min.
	100Hz	-160dBc/Hz Min.
	1kHz	-165dBc/Hz Min.
	10kHz	-165dBc/Hz Min.
Environmental Conditions 工作环境	Operating Temperature Range 工作温度	$-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$
	Storage Temperature Range 储存温度	$-55^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Vibration 振动	Test conditions: Amplitude: 0.75mm (5~26Hz); Acceleration: 10g; 10Hz~500Hz; 30min a cycle, 2 hours in each direction (3 directions, X, Y and Z), IEC68-2-06 Test Fc.	
Shock 冲击	50g; 11ms; Half-sine wave (3 directions, X, Y, and Z), IEC68-2-27TestEa/Severity 50A	
Size 尺寸	36*27*12.7mm	

Note: The specifications are for reference only. Please contact customer service for detailed specifications.